



ARTROM STEEL TUBES S.A.

Draganesti Str. 30, Slatina, jud. OLT, Romania 230119
 Tel: +40 (249) 434640, 434641 Fax: +40 (249) 437288, 430055
 E-mail: office@artrom.com www.artrom.com
 EUID: ROONRC.J1991000009283; J1991000009283; VAT No. RO 1510210/1992
 Subscribed and Paid Share Capital: 291.587.538,34 lei

Tab. 1 Dimensions – Line pipe HOT ROLLING CPE MILL – acc.API 5L & ISO 3183

Nominal	OD		WT		Weight		Lmax		Identification	
	in	mm	in	mm	lb/ft	kg/m	ft	m	STD/XS/XXS	Sch.
1/2	0.840	21.3	0.095	2.41	0.76	1.12	40.0	12.2	STD	30
			0.109	2.77	0.85	1.27				40
3/4	1.050	26.7	0.095	2.41	0.97	1.44	40.0	12.2	STD	30
			0.113	2.87	1.13	1.69				40
1	1.315	33.4	0.109	2.77	1.41	2.09	40.0	12.2	STD	10
			0.114	2.90	1.46	2.18				30
			0.133	3.38	1.68	2.50				40
1 1/4	1.660	42.2	0.109	2.77	1.81	2.69	40.0	12.2	STD	10
			0.117	2.97	1.93	2.87				30
			0.140	3.56	2.27	3.39				40
1 1/2	1.900	48.3	0.109	2.77	2.09	3.11	40.0	12.2	STD	10
			0.125	3.18	2.37	3.53				30
2	2.375	60.3	0.145	3.68	2.72	4.05	40.0	12.2	STD	40
			0.109	2.77	2.64	3.93				10
			0.125	3.18	3.01	4.48				30
			0.141	3.58	3.37	5.01				40
			0.154	3.91	3.66	5.44				STD
			0.172	4.37	4.05	6.03				40
			0.188	4.78	4.40	6.54				80
			0.218	5.54	5.03	7.48				XS
			0.250	6.35	5.68	8.45				
2 1/2	2.875	73.0	0.281	7.14	6.29	9.36	40.0	12.2	STD	10
			0.109	2.77	3.22	4.80				30
			0.120	3.05	3.53	5.26				40
			0.125	3.18	3.67	5.48				40
			0.141	3.58	4.12	6.13				40
			0.156	3.96	4.53	6.74				40
			0.172	4.37	4.97	7.40				40
			0.188	4.78	5.40	8.04				40
			0.203	5.16	5.80	8.63				40
			0.216	5.49	6.14	9.14				40
3	3.500	88.9	0.250	6.35	7.02	10.44	40.0	12.2	STD	80
			0.276	7.01	7.67	11.41				80
			0.125	3.18	4.51	6.72				30
			0.141	3.58	5.06	7.53				40
			0.156	3.96	5.58	8.30				40
			0.172	4.37	6.12	9.11				40
			0.188	4.78	6.66	9.92				40
			0.216	5.49	7.58	11.29				40
			0.250	6.35	8.69	12.93				40
3 1/2	4.000	101.6	0.281	7.14	9.67	14.40	40.0	12.2	STD	80
			0.300	7.62	10.26	15.27				160
			0.438	11.13	14.34	21.35				80
			0.125	3.18	5.18	7.72				30
			0.141	3.58	5.82	8.65				40
			0.156	3.96	6.41	9.54				40
			0.172	4.37	7.04	10.48				40
			0.188	4.78	7.66	11.41				40
			0.226	5.74	9.12	13.57				40
4	4.500	114.3	0.250	6.35	10.02	14.92	40.0	12.2	STD	80
			0.281	7.14	11.17	16.63				40
			0.318	8.08	12.52	18.64				40
			0.125	3.18	5.85	8.71				30
			0.141	3.58	6.57	9.78				40
			0.156	3.96	7.24	10.78				40
			0.172	4.37	7.96	11.85				40
			0.188	4.78	8.68	12.91				40
			0.203	5.16	9.32	13.89				40
			0.219	5.56	10.02	14.91				40
			0.237	6.02	10.80	16.08				40
0.250	6.35	11.36	16.91	40						
0.281	7.14	12.67	18.87	40						
0.312	7.92	13.97	20.78	40						
0.337	8.56	15.00	22.32	40						
0.438	11.13	19.02	28.32	40						