



ARTROM STEEL TUBES S.A.

Draganesti Str. 30, Slatina, jud. OLT, Romania 230119
 Tel: +40 (249) 434640, 434641 Fax: +40 (249) 437288, 430055
 E-mail: office@artrom.com www.artrom.com
 EUID: ROONRC.J1991000009283; J1991000009283; VAT No. RO 1510210/1992
 Subscribed and Paid Share Capital: 291.587.538,34 lei

Tab.1 Coupling stocks dimensions

UPSET TUBING acc. API 5CT		
Specified Outside Diameter of Pipe (D) in (mm)	Outside Diameter	
	<i>in</i>	<i>mm</i>
1.900 (48.26)	2.500	63.50
2 3/8 (60.32)	3.063	77.80
2 7/8 (73.02)	3.668	93.17
3 1/2 (88.90)	4.500	114.30
4 (101.60)	5.000	127.00
4 1/2 (114.30)	5.563	141.30

NON-UPSET TUBING acc. API 5CT		
Specified Outside Diameter of Pipe (D) in (mm)	Outside Diameter	
	<i>in</i>	<i>mm</i>
2 3/8 (60.32)	2.875	73.02
2 7/8 (73.02)	3.500	88.90
3 1/2 (88.90)	4.250	107.95
4 (101.60)	4.750	120.65
4 1/2 (114.30)	5.200	132.08

Casing acc. API 5CT		
Specified Outside Diameter of Pipe (D) in (mm)	Outside Diameter	
	<i>in</i>	<i>mm</i>
4 1/2 (114.30)	5.250	133.35
5 (127.00)	5.800	147.32
5 1/2 (139.70)	6.300	160.02
6 5/8 (168.28)	7.390	187.71
7 (177.80)	7.875	200.03
7 5/8 (193.70)	8.500	215.90
8 5/8 (219.08)	9.625	244.48

Line Pipe acc. API 5L		
Specified Outside Diameter of Pipe (D) in (mm)	Outside Diameter	
	<i>in</i>	<i>mm</i>
2 3/8 (60.3)	2.875	73.0
2 7/8 (73.0)	3.375	85.7
3 1/2 (88.9)	4.000	101.6
4 (101.6)	4.625	117.5
4 1/2 (114.3)	5.200	132.1
5 9/16 (141.3)	6.296	159.9
6 5/8 (168.3)	7.390	187.7

Note: Wall Thickness according to customer's request.

ARTROM STEEL TUBES S.A. Cod: FCU-01, Ed. 5 Rev. 3/2025

LRQA:
 ISO 9001
 ISO 14001
 ISO 45001

LRQA:
 IATF 16949

TUV:
 PED/AD-2000 W0/W4
 Vd TUV

TUV CPR:
 EN 10210-1,2
 EN 10255

DNV
 RINA
 LR